



STRAND FEEDER

We've redesigned the IHS Strand Feeder to improve the safety and usability of the unit. All of the electrical switches, inlets and outlets have been moved to the front of the unit.

Features

- Forward & reverse toggle
- 240V input & output
- External RCD test & reset buttons
- Threaded strand openings to allow for camlock connections
- Mechanical strand tensioner - drive options of 32mm A/F hex, 1/2" square and 3/8" rod
- Collapsible twin carry handles
- Removable weather cover
- Optional pendant control

Specifications

Input: 240V
 Output: 240V
 Strand: 12.7 (0.5") & 15.2 (0.6")
 Speed: 150m/min
 Dimensions: 500mm (l) x 320mm (w)
 x 455mm (h)
 Weight: 55kg

Ordering Information

Part No.	Description
IHS-SF	IHS Strand Feeder
IHS-SF-P	IHS Strand Feeder w/Pendant Control

Accessories / Spares

Part No.	Description
IHS-SF-ROLLER	Roller
IHS-SF-ROLLERSP	Roller Sprocket
IHS-SF-MOTORSP	Motor Sprocket
IHS-SF-BEARING	Bearing
IHS-SF-SHROUD-__	Protective Shroud - Length cut to customer requirements



T
N
E
M
P
I
U
Q
E
G
N
I
S
S
E
R
T
S
H
H

P: +61 3 9645 1522 | E: mail@mcmillaneng.com.au | W: www.mcmillaneng.com.au